

# tesa<sup>®</sup> Duct Tape

## Extra Power Universal

### 56388/56348/56389/56490



#### Product Information

tesa<sup>®</sup>56388 Extra Power Universal is a multipurpose cloth tape. It consists of a polyethylene film and a woven polyester fabric backing coated with a synthetic rubber adhesive. tesa<sup>®</sup> 56388 Extra Power Universal is a self-adhesive tape with typical duct tape features for a wide range of applications.

- Excellent adhesion even on rough surfaces (e.g. brickwork, timber)
- Easy to tear by hand with straight edges
- Waterproof & weather-resistant
- Moisture resistant
- Smooth & comfortable
- Solvent free
- Available in 4 colors: black, white, gray, green

#### Main Application

- For simple, everyday solutions and quick and easy repairs
- For handicrafts, repairing, fastening, bundling, strengthening, marking and much more!

#### Technical information (average values)

The values in this section should be considered as average figures or typical only and should not be used for specification purposes.

#### Technical Data

- |                       |                  |                    |                                    |
|-----------------------|------------------|--------------------|------------------------------------|
| • Total thickness     | 220 µm           | • Backing          | PET fabric, laminated with PE-film |
| • Elongation at break | 30 %             | • Tensile strength | 100 N/25mm                         |
| • Adhesive            | Synthetic rubber |                    |                                    |
| • Adhesion to steel   | 23 N/25mm        |                    |                                    |

#### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you