



# tesapack<sup>®</sup> Paper Standard ecoLogo

## Product Information



BNR 58291, 58292, 58293

## Product Description

Made from 56% bio-based materials, tesapack<sup>®</sup> PAPER STANDARD is a paper adhesive tape that makes recycling easy. The paper used for this highly versatile tape comes from sustainably managed forests and the adhesive is made from natural rubber.

## Product Features

- tesapack Paper Standard: This environmentally friendly paper adhesive tape is ideal for packaging and sealing light to medium-weight cardboard up to 10 kg
- Extremely versatile: The parcel tape offers strong adhesion on smooth and rough surfaces and is suitable for manual or automatic packaging tape dispensers
- Sustainable: tesa Paper Standard packing tape is made with paper from well-managed, FSC<sup>®</sup>-certified forests and other controlled sources (FSC<sup>®</sup> C148769) and can be disposed together with the cardboard box
- Durable paper for a secure seal: The adhesive tape is humidity-resistant - at the same time, it can be torn off by hand and is easy to unroll

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- |                                  |       |                    |                |
|----------------------------------|-------|--------------------|----------------|
| • Bio-based (bio-carbon content) | 58 %  | • Type of adhesive | natural rubber |
| • Backing material               | Paper | • Total thickness  | 125 µm         |
| • Bio-based (bio-carbon content) | 58 %  |                    |                |

## Properties/Performance Values

- |                          |                   |                       |        |
|--------------------------|-------------------|-----------------------|--------|
| • Elongation at break    | 10 %              | • Low noise unwinding | yes    |
| • Tensile strength       | 33 N/cm           | • Solvent free        | yes    |
| • Adhesive strength      | Standard adhesion | • Tear resistance     | no     |
| • Ageing resistance (UV) | no                | • Unwind force n/cm   | 3 N/cm |
| • Hand tearability       | yes               |                       |        |

## Certificates

**Certified according to**  
FSC<sup>®</sup> C148769, INGEDE12

For latest information on this product please visit <http://l.tesa.com/?cp=58291>



# tesapack<sup>®</sup> Paper Standard ecoLogo

Product Information

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=58291>


## tesa® Paper Standard – 58291, 58292, 58293

tesa® Paper Standard is a general-purpose packaging tape based on a fine crepe paper backing and a natural rubber adhesive. The paper backing of tesa® Paper Standard is made with paper from well-managed, FSC®-certified forests and other controlled sources. The natural rubber adhesive system features good adhesion to multiple surfaces as well as good tack.



## Main Application

- Sealing of light-weight cardboardes
- Good adhesion in recycled cardboards
- Suitable for manual and automatic dispensers
- Recycling-friendly tape according to INGEDE Method



## Technical Data & Properties

<b>Dimensions</b>	50 m : 50 mm 3 x 50 m : 50mm 25 m : 38 mm
<b>Color</b>	Brown
<b>Backing</b>	FSC®-certified paper
<b>Type of Adhesive</b>	Natural Rubber
<b>Backing Thickness</b>	94 µm
<b>Total Thickness</b>	125 µm
<b>Adhesion/Steel</b>	2,8 N / cm
<b>Tensile Strength</b>	30 N / cm
<b>Elongation at break</b>	10 %

For the latest information on this product please visit <http://www.tesa.com/consumer>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

## Additional Information & Pictures



58291



58292



58293

## IBNR´s

IBNR	Description
58291	tesa® Paper Standard 50:50
58292	3x tesa® Paper Standard 50:50
58293	tesa® Paper Standard 25:38

For the latest information on this product please visit <http://www.tesa.com/consumer>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.